

/ :  
 :  
 / .  
 : 06 /2018

μ μ -  
 : 17/07-09-2016 ( : 75 46530 - 2 ), 26/ 04-10-2012 ( : 4 81-70 )

	μ.		1501- +	( 17/07-09-2016)	
μ					
10.01.01	001	, μ			
10.01.02	002	μ μ , μ			
10.03	003	μ			
10.04	004	μ μ			
10.07.01	005	μ μ			
20.04.01	006	E μ - μ μ	02-04-00-00		
20.05.01	007	E μ - μ μ μ μ	02-04-00-00		
20.06.03	008	μ μ μ μ 2,00 m			
20.08.01	009	- μ	02-04-00-00		
20.10	010	μ , μ	02-07-02-00		
20.20	011	μ μ			
20.21	012	μ	02-07-02-00		
20.30	013	μ μ μ			
20.31.02	014	μ μ , μ			
\20.50.08	015	( EKK) ,			
22.04	016	μ	14-02-02-01		
22.10.01	017	μ , μ	15-02-01-01		
22.15.01	018	μ μ μ μ ,	15-02-01-01		
22.20.01	019				

	μ.		1501- +	( 17/07-09-2016)	
μ					
22.20.02	020	μ 50%			
22.23	021	μ	14-02-01-01		
22.30.03	022	, μ 0,12 m2 0,25 m2 μ ,			
22.30.04	023	, μ 0,25 m2 0,50 m2 μ ,			
22.31.02	024	0,10 m 0,20 m μ ,			
22.37.02	025	μ 0,10 m 0,20 m μ ,			
22.45	026	μ			
22.50	027				
22.52	028	μ			
22.53	029				
22.54	030	μ	14-02-01-01		
22.56	031	μ	15-02-02-02		
22.60	032				
22.61	033	μ			
22.65.02	034	μ μ μ			
22.70.01	035	μ μ μ μ			
22.70.02	036	μ μ μ μ			
\22.60.1	037	μ μ			
23.03	038	μ	01-03-00-00 *	μ	01-03-00-00
23.10.02	039	μ ( ), μ 200 kg			
23.14	040	μ			
5.07	041	μ μ μ μμ	08-01-03-02 *	μ	08-01-03-02

	μ.		1501- +	( 17/07-09-2016)	
μ					
32.01.04	042	μ , μ μ , μ μ μ C16/20	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
32.01.05	043	μ , μ μ , μ μ μ C20/25	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
32.05.03	044	μ μ C12/15			
32.05.04	045	μ μ C16/20			
32.25.03	046	μ μ μ , 30,00m3 μ C16/20			
38.02	047	μ	01-04-00-00		
38.20.03	048	μ μ , μ μ B500C	01-02-01-00 *	μ μ	01-02-01-00
10.01.02	049	μ μ μ μ	08-05-02-01		
10.18	050	μ μ			
10.19	051	μ μ μ μ			
10.23	052	μ μ μ (0,3 - 3,00 mm) μ	14-01-07-01		
46.01.03	053	6x9x19 cm, μ μ 1 (μ ) (μ )	03-02-02-00 *	μ	03-02-02-00

	μ.		1501- +	( 17/07-09-2016)	
μ					
46.01.02	054	6x9x19 cm, μ μ 1/2 ( μ μ )	03-02-02-00 *	μ	03-02-02-00
49.01.01	055	μ ( μ ) μ μ			
49.01.02	056	μ ( μ ) μ μ			
49.05	057	μ μ μ			
50.10	058	μ μ μ μ μ			
50.15.02	059	μ μ , μ μ			
\79.11.1	060	μ μ			
71.21	061	μ - μ μ μ	03-03-01-00		
78.05.01	062	, , 12,5 mm			
78.05.03	063	, , 18 mm			
78.05.04	064	, , 12,5 mm			
78.05.05	065	, , 12,5 mm			
78.10.02	066	μ , 12,5 mm			
78.30.01	067	μ , μ , 15 20 mm, 600x600 mm 625x625 mm	03-07-10-01		
78.30.03	068	μ 12 , μ , 13 mm, μ μ 600x600 mm	03-07-10-01		
78.34	069		03-07-10-01		
\8042.1.3	070	μ 100. P.V.C. 6atm			
\8042.1.4	071	μ 125 P.V.C. 6atm			
\8051.1.1	072				
\8051.1.2	073	μ μ μ μ			
\8051.1.4	074	μ μ μ μ			
\8104.1	075	( ) μ. 1/2ins			
\8104.2	076	( ) μ. 3/4ins			
\8104.3	077	( ) μ. 1ins			

	μ.		1501- +	( 17/07-09-2016)	
μ					
\8104.4	078	( ) μ. 1 1/4 ins			
\8104.5	079	( ) μ. 1 1/2 ins			
\8104.7	080	( ) μ. 2 ins			
\8104.8	081	( ) μ. 2 1/2 ins			
\8104.9	082	( ) μ. 3 ins			
\8104.10	083	( ) μ. 4 ins			
8141.2.2	084	μ (μ ) μ - , μ 1/2 ins			
8141.3.2	085	μ (μ ) μ - , 1/2 ins μ μ			
8151.2	086	μ μ μ			
8157.1	087				
\8158	088	μ			
8160.2	089	42 56 cm			
8160.5	090				
\8160.6	091				
8166.1	092	μ			
\8204.99.1	093	(sprinkler) μ. 1/2 ins			
\8432.1.2	094	μ μ PANEL 22/600/600			
\8432.1.3	095	μ μ PANEL 22/600/800			
\8432.2.2	096	μ μ PANEL 22/900/600			
\8432.2.3	097	μ μ PANEL 22/900/800			
\8432.6.1	098	(FCU) μ μ 300 CFM, - , ,			
\8432.6.2	099	(FCU) μ μ 400 CFM, - , ,			
\8432.6.3	100	(FCU) μ μ 600 CFM, - , ,			
\8432.6.4	101	(FCU) μ μ 800 CFM, - , ,			
\8445.3	102	μ μ			
8732.2.2	103	μμ 13,5mm			
8732.2.4	104	μμ 23mm			

	μ.		1501- +	( 17/07-09-2016)	
μ					
\8732.1	105	2,5 2,5cm	μμ .		
\8732.2	106	4,0 4,0cm	μμ .		
\8732.3	107	6 10cm	μμ .		
8735.2.1	108	70mm			
8751.1.2	109	μ 1,5 mm2			
8751.1.3	110	μ 2,5mm2			
\8766.2.1	111	2 1,5 mm2			
\8766.3.4	112	3 6 mm2			
\8766.3.5	113	3 10 mm2			
\8766.5.2	114	5 2,5 mm2			
\8766.5.4	115	5 6 mm2			
\8774.5.6	116	Y 4 16 mm2			
\8797.1.1	117	A-2Y(st)2Y			
\8797.1.1.1	118	UTP CAT 5E			
\8797.1.2	119	μ μ			
8801.1.1	120	10 μ 10 250 V			
8801.1.4	121	10 μ 10 250 V			
\8801.1.1	122	μ 250 V			
\8806.1.1	123	10 , 250 V			
8826.3.2	124	μ SCHUKO 16			
\8828.1	125	μ			
\8843.1.1	126	18- 36			
\8843.1.1.3	127	54-72			
\8843.2.1.1	128	24 44			
\8843.2.1.2	129	μ 24			
\8916.4.1	130	μ ( )			
\8919.1	131	24- μ			
\8971.1.3	132	μ μ μ 1 36W, μ .			

	μ.		1501- +	( 17/07-09-2016)	
μ					
\8971.1.4	133	μ μ 2 36W, μ .			
\8972.1.4	134	μ μ 2 36W, μ μ .			
\8977.2.2	135	μ μ , 4 18W			
\8977.2.3	136	μ μ , 4 18W			
\8977.2.4	137	μ μ μ , 54, 2 36W.			
\8978.2.1	138	μ μ 18-36W.			
\8979.2	139	μ μ μ			
\8979.3	140	μ μ μ			
\8980.41	141	9W			
\8981.1	142	Ballast Osram Quicktronic Professional			
\8983.10.1.1	143	μ μ μ μ ,			
\8987.1	144				
.9200.1.1	145	AV1) , grundfos (KP 350			
.9200.1.2	146	μ μ - μ grundfos ( UNILIFT P 50 )			
\9083.1	147	0,75HP			
16.09	148	μ μ μ	08-06-08-03 *		08-06-08-03
16.11	149	.	08-06-08-03 *		08-06-08-03
16.12	150		08-06-08-03 *		08-06-08-03
16.13	151		08-06-08-03 *		08-06-08-03
\8919.3	152	7 μ μ			
11.01.01	153	K μ μ (gray iron)			
11.02.01	154		08-07-01-01		
11.01.02	155	K μ μ (ductile iron)			

	μ.		1501- +	( 17/07-09-2016)	
μ					
11.02.03	156	μ , μ , ,	08-07-01-03		
12.10.03	157	μ PVC-U μ PVC-U, SDR 41, DN 160 mm	08-06-02-02 *	-PVC	08-06-02-02
12.10.04	158	μ PVC-U μ PVC-U, SDR 41, DN 200 mm	08-06-02-02 *	-PVC	08-06-02-02
16.30.01	159	μ μ μ ) μ (μ μ			
16.40.01	160	μ μ μ μ DN 200-300 mm			
\8151.90	161	μ / μμ (μ μ )			
8174	162	μ μ			
8175.1	163	( ) ,			
8177	164	μ			
8178.1.2	165	μ μ μ			
8179.2	166	μ μ μμ μ			
8256.6.1	167	μ 80 l 3000 W			
8538.1 1	168	μ (SPLIT- SYSTEM), - μ , μ 9.000 BTU/H			
8538.1 2	169	μ (SPLIT- SYSTEM), - μ , μ 12.000 BTU/H			
\7319.1.1	170	μ μ 10,4x10,4cm, 6cm.			
72.31.02	171	μ μ μ , , 1,00 mm	03-05-02-01		
72.70	172	μ			
73.16.02	173	μ μ , 30 cm			
73.26.03	174	μ , μ , 15x15 cm,	03-07-02-00		
73.31.03	175	μ ( μ μ μ μ (μ ) μ ( ) , 20x10 cm,	03-07-02-00		
73.33.01	176	μ μ , GROUP 4, 20x20 cm	03-07-02-00		



	μ.		1501- +	( 17/07-09-2016)	
μ					
73.33.02	177	30x30 cm μ μ , GROUP 4,	03-07-02-00		
73.34.01	178	20x20 cm μ μ GROUP 1,	03-07-02-00		
73.35	179	( ) μ			
73.37.02	180	μ - - μ μ μ μ 1,5 cm			
73.47	181	μ ( )			
73.59.02	182	2,5 cm μ μ , μ μ			
73.75	183	( ) μ			
73.76	184	μ μ μ μ μ			
73.87	185	μ μ			
73.96	186	μ (PVC)	03-07-06-02		
73.97	187	μ	03-07-06-02		
73.96	188	μ LINOLEUM			
74.23	189	μ μ			
74.30.01	190	μ , 2 cm, μ 5 μ μ ,	03-07-03-00 *	μ	03-07-03-00
74.30.02	191	μ , 2 cm, μ 6 10 μ μ ,	03-07-03-00 *	μ	03-07-03-00
74.23	192	μ μ μ μ			
75.21.03	193	2 cm ( ) μ μ μ μ ,	03-07-03-00 *	μ	03-07-03-00
75.21.04	194	( ) μ μ μ , 2 cm 20 cm	03-07-03-00 *	μ	03-07-03-00
75.61.03	195	μ μ μ μ μ 2,00 m, 2 cm	03-07-04-00 *	μ (μ μ . )	03-07-04-00
75.66.01	196	μ μ μ μ 2 cm μ , μ	03-07-04-00 *	μ (μ μ . )	03-07-04-00
77.02.01	197	μ μ 5% μ	03-10-02-00		
77.10	198	μ μ μ μ μ μ μ	03-10-01-00		

	μ.		1501- +	( 17/07-09-2016)	
μ					
77.17.01	199	μ μ μ μ ,	03-10-02-00		
			03-10-05-00		
77.18	200	μ μ	03-10-02-00		
77.20.02	201	μ , μ , μ	03-10-03-00		
77.30	202	μ ( ) μ μ	03-10-02-00		
77.33	203	μ μ	03-10-03-00		
77.95	204	(antigraffiti) μ μ ,	05-02-03-00		
77.102	205	μ μ , μ μ			
\77.55	206	μ μ μ μ	03-10-03-00		
\77.66	207	μ μ μ μ μ μ μ ? 80 C	03-10-03-00		
\77.70	208	μ μ			
\77.71.01	209	μ μ μ μ , μ μ ,	03-10-05-00		
78.91	210	μ μ μ			
79.05.1	211	μ μ μ μ μ μ	08-05-03-03 *	μ μ / μ μ μ μ	08-05-03-03
79.08	212	μ μ			
79.10	213	μ μ μ μ μ			
79.11.01	214	μ μ μ μ μ , μ μ μ	03-06-01-01 *	μ - μ μ μ	03-06-01-01
79.11.02	215	μ μ μ μ μ (APP), μ μ μ	03-06-01-01 *	μ - μ μ μ	03-06-01-01
79.11.03	216	μ μ μ μ μ , μ μ μ 0,08 mm	03-06-01-01 *	μ - μ μ μ	03-06-01-01

	μ.		1501- +	( 17/07-09-2016)	
μ					
79.12.01	217	μ (EPDM) μ μ , μ μ	03-06-01-02		
79.12.02	218	μ μ μ , μ μ PVC - P μ	03-06-01-02		
79.15.03	219	μ μ , 205 gr/m2			
79.18	220	μ HDPE μ ( )			
79.40	221	μ μ 50 mm			
79.46	222	μ μ μ 50 mm	03-06-02-01 *	μ μ μ	03-06-02-01
79.47	223	μ μ μ 50 mm μ	03-06-02-02 *	μ μ	03-06-02-02
79.55	224	μ - μ μ μ 50 mm	03-06-02-02 *	μ μ	03-06-02-02
\ 78.70.1	225	μ μ 50cm			
54.46.01	226	13 cm μ μ ,	03-08-01-00		
54.46.02	227	23 cm μ μ ,	03-08-01-00		
55.01.01	228	μ			
56.21	229	μ DUROPAL			
56.23	230	μ μ μ	03-09-01-00		
56.24	231	μ μ , μ μ	03-09-01-00		
61.04	232	, , μ 16 cm			
61.05	233	160 mm			
61.12	234	μ μ			
61.13	235	μ μ			
61.30	236				
62.60.01	237	μ , μ , μ 30 min			
62.60.02	238	μ , μ , μ 60 min			
62.60.03	239	μ , μ , μ 90 min			
64.03	240	μ			
64.16.01	241	μ μ , 1"			

	μ.		1501- +	( 17/07-09-2016)	
μ					
64.16.02	242	μ , 1 1/2 "			
64.16.03	243	μ , 2"			
65.01.03	244	μ μ μ μ 12 kg/m2	03-08-03-00 *	μ μ	03-08-03-00
65.01.04	245	μ μ μ μ 12 24 kg/m2	03-08-03-00 *	μ μ	03-08-03-00
65.02.01.01	246	μμ μ , μ ,	03-08-03-00 *	μ μ	03-08-03-00
65.32	247	μ			
\65.41.01	248	μ			
72.47.02	249	μ , μ 100 mm			
\72.47.01	250	μ , μ 50 mm			
76.01.02	251	μ , 4,0 mm	03-08-07-01		
76.01.03	252	μ , 5,0 mm	03-08-07-01		
76.20.02	253	μ , 6,50 mm μ 1,00 m	03-08-07-01		
76.22.01	254	(LAMINATED), 6 mm (3 mm + μ μ + 3 mm)	03-08-07-02		
76.27.01	255	μ μ - μ - 18 mm, ( 5 mm, 8 mm, 5 mm)	03-08-07-02		
76.27.02	256	μ μ - μ - 22 mm, ( 5 mm, 12 mm, 5 mm)	03-08-07-02		
76.35.01	257	Securit, μ 8,0 mm	03-08-09-00		
76.21	258	μ μμ			
76.22.03	259	(LAMINATED), 12 mm (4 mm + μ μ + 4 mm + μ μ + 4 mm)	03-08-07-02		
76.25	260	SECURIT 10 mm	03-08-07-02		
76.27.03	261	μ μ - μ - 25 mm, ( 5 mm, 12 mm, laminated 4 mm + 4 mm)	03-08-07-02		
.65.01.1	262	( ) μ μ	03-08-03-00 *	μ μ	03-08-03-00
.65.01.2	263	μ μ μ	03-08-03-00 *	μ μ	03-08-03-00

	μ.		1501- +	( 17/07-09-2016)	
μ					
.65.01.3	264	μ /	03-08-03-00 *	μ μ	03-08-03-00
.65.01.4	265	μ / μ μ	03-08-03-00 *	μ μ	03-08-03-00
.65.01.5	266	μ / μ μ 90 μ	03-08-03-00 *	μ μ	03-08-03-00
.65.01.7	267	μ ( )	03-08-03-00 *	μ μ	03-08-03-00
.65.01.8	268	μ ( )	03-08-03-00 *	μ μ	03-08-03-00
78.13	269	μ			
78.21	270	μ μ μ			
79.37	271	μ μ μ	08-05-02-05		
79.38	272	μ μ μ	08-05-02-05		
79.95 1	273	μ μ μ μ	08-05-03-03 *	μ μ / μ μ μ μ	08-05-03-03
.77.97	274	μ μ ,	03-10-01-00		
.77.98	275		03-10-01-00		
\14.04.01	276				
μ					
78.70		μ μ	03-07-08-00		

-02-2018

-02-2018

-02-2018

Н .

μ μ

μ μ

μ μ